

LITTORA 1000 ICW SUB10

Product sheet

This subwoofer is the perfect partner in any system, offering power and dynamics, even at high volumes. The more there are, the more the effect is increased. Its very shallow mounting depth and its 10-inch (25.4cm) diameter make the product easy to conceal within a system. Like a dive watch, it has been rigorously developed to perfectly suit being used in extreme conditions, such as yachting or for outdoor or indoor use at home. This speaker driver is characterised by excellence and versatility. The power and refinement of the Focal sound in all conditions, no compromise.



Technical specifications

Type of speaker	LITTORA 1000 ICW SUB10
Diameter	10"
Recommended amplifier power	100 - 300W
Nominal impedance	8 ohms
Minimal impedance	4 ohms at 85Hz
Sensitivity (2.83V/1m)	90dB
Frequency response	25Hz - 500Hz
IP certification	IP65 (ASTMB117)
Grille	Aluminium ready-to-paint
UV resistance	Yes (ASTMG53)
Operating temperatures	-25°C to 90°C
Number of mounting points	8
Connector	Etanche DT06-2S
Mounting depth	4 ^{7/8} " (123mm)
Certifications	ROHS, ROHS 2, ROHS CHINE, REACH

Key points

- High-fidelity sound and excellent power handling
- Developed in France
- Certified IP65 waterproofing
- Ready-to-paint white aluminium grille for limitless customisation
- Shallow mounting depth

Size (mm)

