

Viewline Wastewater Level Gauges

Description

Indication of Wastewater Tank levels.



Picture: Wastewater Level Gauge

Features

- _ LED illumination
- _ Integrated Warning LED
- _ Changeable bezels
- _ Backlit technology
- _ Antifog and splash protection
- _ Panel and flush mount possibility

Concept

| | |
|--------------|---|
| Housing | Polycarbonat (PC) |
| Bezel | PC (black, white) or ABS (chrome); several colors and shapes (see table) |
| Lens | PMMA; double lens |
| Dial | backlit; different colors (black, white) |
| Pointer | backlit, white on black dials; red on white dials |
| Illumination | Dial: LED amber (605nm) Pointer: LED red (632nm) |
| Warning LED | red (632nm), Wastewater Gauges only with optional PC software adjustable |
| Mounting | Spinlock Nut; locking height 0.5mm – 20mm, Optional Studs and Bracket; locking height 2 – 15mm |
| Connection | 8 pin MQS connector system |
| Sensor | Wastewater: N02-240-902, N02-240-904, N02-240-906 |

| Technical Data | | |
|---|--|---|
| Installation depth | 50mm | |
| Installation diameter | 52mm | |
| Deflection angle | 240° | |
| Operating Voltage | 8 – 32 Volt | |
| Accuracy | < 2,5 % of the full scale reading at 13.0 Volt | |
| Current consumption | < 140 mA, including Warning LED | |
| Operating temperature | -30°C to +80°C; plated bezels (chrome) -30°C to +70°C | |
| Storage temperature | -40°C to +80°C for 48h; plated bezels (chrome) -40°C to +70°C +90°C for 1h | |
| Temperature shock | Range Transformation time Retention time | -40°C to +85°C; plated bezels (chrome) -40°C to +70°C 10 seconds 2h |
| Climatic test | Range Rel. Humidity | +25°C to +55°C 95% |
| EMC in conformity with (Electromagnetic compatibility) | DIN_EN 61000-6-2 DIN_EN 61000-6-3 | |
| Standards | CE | |
| Vibration | Sinus 2g; 10-500Hz; duration 16h Noise 3g; 10-1000Hz, duration 8h | |
| Mechanical shock | continuous Single shock Free fall | 25g; 6ms; 1Hz 100g; 11ms 1m; 3 times |
| Chemical resistance against | <ul style="list-style-type: none"> - preservative agent - preservative agent remover - cold cleaner - methylated spirit - interior cleaner - drinks containing caffeine and tannin | |
| Nominal position | NL 0 to NL 85 (DIN16257) | |
| Protection class | according to IEC 60529 Front: IP67 (in nominal position) Rear: IP52 (in nominal position) | |
| Reverse polarity protection | yes, 5 minute | |
| Over voltage protection | yes, 1 minute | |

Available Gauges:

| No. unpacked * | Dial color | Double Scale | Measurement range | ISO Symbol | Sensor | Voltage | Double lens |
|-------------------|------------|--------------|-------------------|------------|----------|------------|-------------|
| Wastewater | | | | | | | |
| A2C53210834 | black | no | 0 to 1/1 | WASTE | 4 – 20mA | 12/24 Volt | yes |
| A2C53210833 | white | no | 0 to 1/1 | WASTE | 4 – 20mA | 12/24 Volt | yes |

* "No. unpacked" is not a order number.

** Tubular-Type Sensor, adjustable

Accessories:

| | |
|--------------------|--|
| A2C59510854 | VL Mounting Kit (studs and brackets) 52, 85, 110mm |
| A2C59510864 | VL Mounting bracket flush mount |
| A2C53215640 | VL Sealing Ring 52mm flush mount |
| A2C59510847 | Bush housing, 8-pin |
| A2C53324664 | Protective connector cap, 8-pin |
| Tyco No. 539635-1 | Hand pliers |
| Tyco No. 539682-2 | Tool for hand pliers. |
| Tyco No. 1355718-1 | Single contacts 0.14 – 0.22 mm ² tin plated |
| Tyco No. 963729-1 | Single contacts 0.5 – 0.75 mm ² tin plated |
| Tyco No. 1355717-1 | Strip 0.14 – 0.22 mm ² tin plated |
| Tyco No. 928999-1 | Strip 0.25 – 0.5 mm ² tin plated |
| Tyco No. 963715-1 | Strip 0.5 – 0.75 mm ² tin plated |

Bezels 52mm

| | Black | Chrome | White |
|-----------------|-------------|-------------|-------------|
| Flat | A2C53186040 | A2C53186023 | A2C53186022 |
| Round | A2C53186027 | A2C53186029 | A2C53186028 |
| Triangle | A2C53186024 | A2C53186026 | A2C53186025 |